SJC Series

Pleated Jumbo Cartridges





- Available in 0.35 to 100 micron ratings
- Large diameter, single cartridge construction makes installations and change outs simple and quick with minimal handling
- High media surface area for maximizing service life and optimizing filter performance and value
- Rugged construction designed for residential, commercial and industrial use
- Compatible with wide range of potable water and aqueous industrial applications
- · Available in three sizes for flow rates up to 150 GPM
- 20 micron and above cartridges may be washed and reused

Applications

RO Prefilters Food & Beverage
Process Water Bottled Water

Swimming Pools Spas

Plating Solutions Water & Wastewater

Specifications & Operating Parameters

Pore Sizes

1A, 0.35, 1, 5, 20, 50 and 100 microns

Nominal Lengths

40 series 9 5/8" (24.5 cm) 90 series 19 1/2" (49.5 cm) 170 series 30 1/4" (76.8 cm)

Outside Diameter

7 3/4" (19.68 cm)

Materials of Construction

Filter Media: Polypropylene / Polyester Blend

Inner Core: PVC

End caps: Polyurethane

Operating Temperature Range:

40°F (4.4°C) – 140°F (60°C)

Recommended Change-out Differential Pressure

20-25 psid (1.4 -1.7 bar)

Maximum Flow Rates Per Cartridge – GPM (LPM)

Series			
Micron	40	90	170
1A	20 (75.7)	40 (151.4)	80 (302.8)
0.35	25 (94.6)	50 (189.3)	100 (378.5)
1	30 (113.6)	60 (227.2)	120 (454.2)
5	50 (189.3)	100 (378.5)	150 (567.8)
20	50 (189.3)	100 (378.5)	150 (567.8)
50	50 (189.3)	100 (378.5)	150 (567.8)
100	50 (189.3)	100 (378.5)	150 (567.8)

Filter Removal Efficiency

Flow vs. Pressure Drop PSI 1A µm 10 0.35 µm 9 1 µm 8 5 µm PRESSURE DROP 20 µm $50 \mu m$, $100 \mu m$ 3 2 100 150 GPM 50

GALLONS PER MINUTE

Ordering Guide (Example: SJC-170-5)

SJC -	- 170	- 5
MODEL	SERIES	MICRONS
SJC	40 90 170	1A 0.35 1 5 20 50 100

Filter Housings

Shelco manufactures a full line of filter housings. From our rugged single cartridge housings to our heavy duty multi-cartridge housings and bag filter housings, Shelco is the perfect choice for your filtration solutions.

For more information, contact Nancrede Engineering

EMAIL: info@nancrede.com

PHONE: +1 888 56-WATER (569-2837) WEB: www.necoindustrialwater.com